



Papilio Static Film – Product information

General product information:

- Is a specifically structured electrically charged polypropylene film.
- Is produced so that electrical charge is stable.
- Is coated with porous special coating which absorbs printing ink solvent.

Product properties:

- This product has no adhesives, it adheres to surfaces with stable electrical charge and it can be printed in offset, digital printing machines and with multitask office printers.
- The film is adhered to paper backer so that it is easy to remove.

Properties: Thickness (μm) Basis weight (g/m^2)

Film	50	45
Paperback	154	200
Total	204	235

Solutions:

- Posters, magazine inserts, greeting cards, calendars, and marketing materials.

Technical information for salesman:

- Is coated with special coating and could be printed on this side.
- The film can be printed in offset, digital printing machines and with multitask office printers.
- Sheet formats: SR2, SR3, 305 x 450 mm, A3, A4.
- Is removed from backing paper before use.
- Is environmentally friendly and recyclable
- Is recommended for indoor use.
- The film adheres to walls, doors, and windows.
- It adheres to virtually any smooth and clean surface

Print settings:

- Recommended HP Indigo settings:
 - Type = Silk / Matt
 - Coating = coated
 - Thickness = 0,25
 - Weight = 235 gsm
 - Heat = 140 degrees Celcius
 - Max. air blowing at the start
 - Driving end to the stacker
- Standard HP inks

- Indigo 5000, 5500, 7000 and 7500 series (sheetfed) are compatible.
- Currently testing Indigo roll equipment
- Not recommended for Indigo 3050 and 3500 (different ink system – no longer supported by HP)
- Only two hits with white color on the Indigo – CLEAR sheet
- Wait 24 hours to cut and pack the labels after printing with white color on the clear Indigo sheet